

View Online at <https://aerobasegroup.com/nsn/5935-01-334-1347>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.759 inches

**Overall Height:**

1.573 inches

**Overall Width:**

1.573 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.128 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.250 inches

**Distance From Mounting Shoulder To Front Face:**

0.702 inches

**Mating End Quantity:**

1

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 200.0 degrees celsius

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and nickel

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification 1st treatment response and mil-c-26074, grade b military specification 2nd treatment response

**Shell Material Specification:**

Qq-a-225/6 federal specification single material response or qq-a-225/8 federal specification single material response

**Special Features:**

Will accept all different polarity plugs of same shell size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-26074 spec.