

View Online at <https://aerobasegroup.com/nsn/5935-01-334-1347>

Body Style:

Straight shape, external coupling

Overall Length:

0.759 inches

Overall Height:

1.573 inches

Overall Width:

1.573 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.128 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Distance From Mounting Shoulder To Front Face:

0.702 inches

Mating End Quantity:

1

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and nickel

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification 1st treatment response and mil-c-26074, grade b military specification 2nd treatment response

Shell Material Specification:

Qq-a-225/6 federal specification single material response or qq-a-225/8 federal specification single material response

Special Features:

Will accept all different polarity plugs of same shell size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26074 spec.