## NSN 5935-01-334-4737

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-334-4737

**Body Style:** 

Straight shape

**Overall Length:** 

2.425 inches

**Overall Height:** 

0.320 inches

**Overall Width:** 

Between 0.315 inches and 0.320 inches

**Environmental Protection:** 

Shock resistant and vibration resistant and moisture resistant and corrosion resistant

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Connector Locking Method:** 

Friction

**Operating Tempurature Rating:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy 172 single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:** 

Plastic polyphenylene single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-533, temper ht federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-p-46174, cl 40, grade e military specification single material response single mating end

**Included Contact Quantity:** 

96 single mating end single contact grouping

## NSN 5935-01-334-4737

Electrical Plug Connector - Page 2 of 2



Included Contact Type:
Continue simula mastinue and

Spring single mating end single contact grouping

**Special Features:** 

Contact identification numbers are 1 to 48; contacts opposite to each other are shorted

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.096 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.