NSN 5935-01-334-9718

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-334-9718
Body Style:
Right angle type
Overall Length:
5.240 inches
Overall Height:
0.288 inches
Overall Width:
0.535 inches
Environmental Protection:
Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.093 inches and 0.098 inches
Distance Between Mounting Facility Centers:
5.075 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
300.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -55.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy 260 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-01-334-9718

Electrical Receptacle Connector - Page 2 of 2



Criticality Code Justification:
Feat
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-613, 1/2 hard federal specification single material response single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Chromate
Shell Surface Treatment Specification:
Mil-c-5541, cl 3 military specification single treatment response
Shell Material Specification:
Qq-a-200 federal specification single material response or qq-a-225 federal specification single material response
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response single mating end
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
96 single mating end single contact grouping
Included Contact Type:
Flat pin single mating end single contact grouping
Special Features:
Widest part of blade contact rotated 90 degrees to housing shield
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.096 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.