

View Online at <https://aerobasegroup.com/nsn/5935-01-334-9718>

Body Style:

Right angle type

Overall Length:

5.240 inches

Overall Height:

0.288 inches

Overall Width:

0.535 inches

Environmental Protection:

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.093 inches and 0.098 inches

Distance Between Mounting Facility Centers:

5.075 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -55.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy 260 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-613, 1/2 hard federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Chromate

Shell Surface Treatment Specification:

Mil-c-5541, cl 3 military specification single treatment response

Shell Material Specification:

Qq-a-200 federal specification single material response or qq-a-225 federal specification single material response

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

96 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Special Features:

Widest part of blade contact rotated 90 degrees to housing shield

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.096 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.