Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-334-9724

## **Body Style:** Straight shape **Overall Length:** 1.385 inches **Overall Height:** Between 1.146 inches and 1.170 inches **Overall Width:** 3.030 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and corrosion resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.192 inches and 0.202 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.558 inches and 0.566 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.580 inches **Distance From Mounting Shoulder To Front Face:** Between 0.519 inches and 0.534 inches Mating End Quantity: **Contact Position Arrangement Style:** G131 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end and guide pin/socket Shell Type: Solid **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -65.0 degrees celsius and 200.0 degrees celsius **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end

1

## NSN 5935-01-334-9724

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment Specification:** Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Contact Material Specification:** Qq-c-533 federal specification single material response single mating end single contact grouping **Guide Design And Location:** D shape socket left-hand top at 12 oclock and d shape socket right-hand bottom at 12 oclock **Shell Material:** Aluminum alloy 380.0 **Shell Surface Treatment:** Nickel **Shell Surface Treatment Specification:** Mil-c-26074, grade a, cl 3 or 4 military specification single treatment response **Shell Material Specification:** Qq-a-591 federal specification single material response **Included Contact Quantity:** 131 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.131 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.

--