NSN 5935-01-335-8043

Electrical Modular Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-335-8043

Body Style:

Right angle type

Overall Length:

Between 1.840 inches and 1.860 inches

Overall Height:

0.854 inches

Overall Width:

0.527 inches

Environmental Protection:

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.066 inches and 0.071 inches

Distance Between Mounting Facility Centers:

1.650 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Guide pin/socket

Odido pirirocono

Shell Type:Solid

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -50.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Shell Material:

Aluminum alloy 6061 or aluminum alloy 1100

NSN 5935-01-335-8043

Electrical Modular Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625, type 2, cl 2 military specification single treatment response
Shell Material Specification:
Qq-a-200/8, t6 federal specification 1st material response or qq-a-250/1, h14 federal specification 2nd material response
Insert Material Specification:
Mil-m-24519, ty pt military specification single material response single mating end
Included Contact Quantity:
22 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.022 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.