# NSN 5935-01-336-0201

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-336-0201

Body Style:
Straight type
Overall Length:
2.380 inches
Overall Height:
0.556 inches
Overall Width:
0.248 inches
Environmental Protection:
Thermal shock resistant and humidity resistant and vibration resistant and shock resistant and salt water resistant and corrosion resistant
Unthreaded Mounting Hole Diameter:
0.098 inches
Distance Between Mounting Facility Centers:
2.090 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
2.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd
treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

## NSN 5935-01-336-0201

Electrical Receptacle Connector - Page 2 of 2



### **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

### **Included Contact Quantity:**

40 single mating end single contact grouping

### **Included Contact Type:**

Square socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.040 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.