## NSN 5935-01-336-3246

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-336-3246 **Thread Class:** 2g **Thread Direction:** Right-hand **Body Style:** Straight shape, w/strain relief **Overall Length:** 8.476 inches **Environmental Protection:** Humidity resistant and moisture resistant and corrosion resistant and salt water resistant and chemical resistant and dust resistant and shock resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Ascc 16-325 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 243.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:** Finger grip Width Across Flats: Between 2.219 inches and 2.270 inches **Operating Tempurature Rating:** Between -67.0 degrees fahrenheit and 225.0 degrees fahrenheit Thready Qty Per Inch (tpi):

**Thread Size:** 

2.000 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Silver single mating end single contact grouping

## **NSN 5935-01-336-3246**Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy 6061 or aluminum alloy
Shell Surface Treatment:
Oxide aluminum
Shell Material Specification:
Qq-a-270 federal specification 1st material response or qq-a-325 federal specification 2nd material response
Insert Material Specification:
Mil-m-14, ty mfh military specification single material response single mating end
Included Contact Quantity:
16 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.016 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.