

View Online at <https://aerobasegroup.com/nsn/5935-01-336-3248>

Body Style:

Angle shape, pcb type

Overall Length:

2.096 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

0.102 inches

Distance Between Mounting Facility Centers:

1.900 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

3 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

3.0 single mating end all contact groupings

Polarization Method:

Mating end

Connector Locking Method:

Friction

End Application:

5841-01-236-8951 detecting set, radar

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Side single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and copper single mating end all contact groupings or gold single mating end all contact groupings and nickel single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end or plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end all contact groupings and mil-c-14550, cl 4 military specification 2nd treatment response single mating end all contact groupings or mil-g-45204, type 2, cl 1, grade c military specification 3rd treatment response single mating end all contact groupings and qq-n-290, cl 2 military specification 4th treatment response single mating end all contact groupings

Terminal Type:

Printed circuit single mating end all contact groupings

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end all contact groupings or qq-c-533 federal specification single material response single mating end all contact groupings or qq-b-750 federal specification single material response single mating end all

Included Contact Quantity:

46 single mating end 2nd contact grouping

Included Contact Type:

Square socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.048 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.