

View Online at <https://aerobasegroup.com/nsn/5935-01-336-3259>

**Body Style:**

Straight shape

**Overall Length:**

Between 0.293 inches and 0.323 inches

**Overall Height:**

Between 0.314 inches and 0.330 inches

**Overall Width:**

0.200 inches

**Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping and tin single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping and mil-p-81728 military specification 3rd treatment response single mating end single contact grouping

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

**Guide Design And Location:**

V groove socket center at 9 o'clock

**Insert Material Specification:**

Mil-m-14, ty sdc-f military specification single material response single mating end or mil-p-19833, ty gdi-30f military specification single

**Included Contact Quantity:**

2 single mating end single contact grouping

**Included Contact Type:**

Spring pincers single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.002 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-28754 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-28754/37 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.