NSN 5935-01-336-3260

Body Style:

Rectangular shape

Overall Length:

Electrical Modular Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-336-3260

3.631 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.051 inches **Overall Height:** 1.396 inches **Overall Width:** 1.420 inches **Environmental Protection:** Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.590 inches **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid **Connector Locking Method:** Friction **End Application:** Tactical air operations module an/tyq-2 (v) 1 **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold and nickel or gold and copper single mating end single contact grouping **Insert Material:** Plastic polyester glass filled single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, class 1, grade c military specification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment response or mil-g-45204, type 2, class 1, grade c military specification 3rd treatment response and mil-c-14550, class 4 military specification 4th treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:**

Qq-b-626 federal specification single material response or qq-b-750 federal specification single material response or qq-c-530 federal

specification single material response single mating end single contact grouping

Shell Material:

NSN 5935-01-336-3260

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Modular Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and anodize
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
13 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.013 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: