## NSN 5935-01-336-5374

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-336-5374

Body Style:
Straight shape
Overall Length:
0.935 inches
Overall Height:
0.616 inches
Overall Width:
0.308 inches
Unthreaded Mounting Hole Diameter:
Between 0.088 inches and 0.094 inches
Distance Between Mounting Facility Centers:
Between 0.710 inches and 0.720 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
"2, 15" single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end or plastic polyester single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Insert Material Specification:
Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519 military specification 2nd material response
single mating end
Included Contact Quantity:

15 single mating end single contact grouping

## NSN 5935-01-336-5374

Electrical Receptacle Connector - Page 2 of 2



## Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.015 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: -Demilitarization: No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):