

View Online at https://aerobasegroup.com/nsn/5935-01-336-5380

Body Style:
Straight shape
Overall Length:
1.185 inches
Overall Height:
0.429 inches
Overall Width:
0.308 inches
Unthreaded Mounting Hole Diameter:
Between 0.088 inches and 0.094 inches
Distance Between Mounting Facility Centers:
Between 0.960 inches and 0.970 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
25 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end and glass fiber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Cadmium or zinc
Shell Material Specification:
Qq-a-200/8 federal specification single material response

NSN 5935-01-336-5380

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-24519 military specification all material responses single mating end

Included Contact Quantity:

25 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-24519 spec.