### NSN 5935-01-336-5382

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-336-5382

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.099 inches

**Overall Height:** 

Between 1.292 inches and 1.332 inches

**Overall Width:** 

Between 1.292 inches and 1.332 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.123 inches and 0.138 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.062 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

#### **Distance From Mounting Shoulder To Front Face:**

Between 0.815 inches and 0.820 inches

**Mating End Quantity:** 

1

#### **Contact Position Arrangement Style:**

17-35 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

0.0 and 95.0 and 132.0 and 232.0 and 260.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 175.0 degrees celsius

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic epoxy single mating end

## NSN 5935-01-336-5382

Electrical Receptacle Connector - Page 2 of 2



# Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping Terminal Type:

Printed circuit single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416 federal specification single treatment response

**Included Contact Quantity:** 

55 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.055 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.