

View Online at <https://aerobasegroup.com/nsn/5935-01-336-6414>

**Thread Class:**

2a and 2a and 2b

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.700 inches

**Overall Diameter:**

Between 1.980 inches and 2.020 inches

**Distance From Mounting Shoulder To Front Face:**

Between 1.015 inches and 1.045 inches

**Mounting Facility Thickness:**

Between 0.0620 inches and 0.1875 inches

**Threaded Device Type:**

Mounting bushing and back shell

**Mating End Quantity:**

15

**Polarization Method:**

Keyway or multiple keyway and key, multiple key groove

**Insert Position In Deg:**

0.0 and 62.0 and 184.0 and 214.0 and 241.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**End Application:**

2320-01-272-5029 truck tractor

**Thready Qty Per Inch (tpi):**

18 and 18 and 18

**Thread Size:**

1.688 inches

**Insert Material:**

Plastic single mating end and glass single mating end

**Shell Material:**

Aluminum alloy or aluminum alloy 360.0

**Bushing Accommodation Hole Shape:**

Round w/flat

**Thread Series Designator:**

Unef and unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0