

View Online at <https://aerobasegroup.com/nsn/5935-01-336-9024>

Body Style:

Straight shape

Overall Length:

5.595 inches

Overall Height:

0.703 inches

Overall Width:

0.590 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

Between 0.122 inches and 0.127 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

4 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-c-502 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24519, ty gpt-15f military specification all material responses single mating end

Included Contact Quantity:

172 single mating end single contact grouping

Included Contact Type:

Brush pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.172 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/166 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.