Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-336-9024

### Body Style:

Straight shape

### Overall Length:

5.595 inches

# **Overall Height:**

0.703 inches

### **Overall Width:**

0.590 inches

### **Environmental Protection:**

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

# **Unthreaded Mounting Hole Diameter:**

Between 0.122 inches and 0.127 inches

# Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

4 rows of contacts non-inserted board single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

#### **Polarization Method:**

Mating end

### **Connector Locking Method:**

Friction

### Operating Tempurature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic single mating end and glass fiber single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290

federal specification 2nd treatment response single mating end single contact grouping

# Terminal Type:

Printed circuit single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-502 federal specification single material response single mating end single contact grouping

# Insert Material Specification:

Mil-m-24519, ty gpt-15f military specification all material responses single mating end

# Included Contact Quantity:

172 single mating end single contact grouping



#### Included Contact Type:

Brush pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.172 gold grains, troy

### **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-55302/166 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.