NSN 5935-01-336-9038

Thread Class: 2b and 2a

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-336-9038

Thread Direction: Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.294 inches **Overall Diameter:** 2.073 inches **Environmental Protection:** Fungus resistant **Distance From Mounting Shoulder To Front Face:** Between 0.879 inches and 0.910 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.250 inches **Threaded Device Type:** Back shell and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 22-38 single mating end **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 and 15.0 and 47.0 and 150.0 and 331.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **End Application:** Tactical air operations module an/tyq-2 (v) 1 Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 1.500 inches and 1.500 inches **Insert Material:** Plastic diallyl phthalate single mating end **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate

NSN 5935-01-336-9038

Electrical Receptacle Connector Body - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Insert Material Specification:

Mil-p-19833 military specification single material response single mating end

Bushing Accommodation Hole Shape:

Round w/flat

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.