

View Online at <https://aerobasegroup.com/nsn/5935-01-336-9038>

Thread Class:

2b and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.294 inches

Overall Diameter:

2.073 inches

Environmental Protection:

Fungus resistant

Distance From Mounting Shoulder To Front Face:

Between 0.879 inches and 0.910 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.250 inches

Threaded Device Type:

Back shell and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

22-38 single mating end

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0 and 15.0 and 47.0 and 150.0 and 331.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

End Application:

Tactical air operations module an/tyq-2 (v) 1

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.500 inches and 1.500 inches

Insert Material:

Plastic diallyl phthalate single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Insert Material Specification:

Mil-p-19833 military specification single material response single mating end

Bushing Accommodation Hole Shape:

Round w/flat

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.