## NSN 5935-01-336-9915

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-336-9915

**Body Style:** 

Straight shape, pc type

**Overall Length:** 

Between 3.025 inches and 3.045 inches

**Unthreaded Mounting Hole Diameter:** 

0.125 inches

**Distance Between Mounting Facility Centers:** 

2.775 inches

**Board Accommodated Length:** 

2.300 inches single board

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

600.0 single mating end single contact grouping

**Connector Locking Method:** 

Friction

**End Application:** 

6625-01-212-3585 instrument, control

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate glass filled single mating end

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

22 single mating end single contact grouping

**Included Contact Type:** 

Bifurcated accordian leaf spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-01-336-9915

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.022 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.