

View Online at <https://aerobasegroup.com/nsn/5935-01-337-6407>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Hood, top opening w/clamp

Overall Length:

2.935 inches

Overall Height:

2.705 inches

Overall Width:

1.450 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Cable Entrance Diameter:

0.550 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

75 single mating end

Polarization Method:

Jackscrew and shell

Shell Type:

Hood, top opening

Connector Locking Method:

Jackscrew-socket

Connector Cable Strain Relief Method:

Cable clamp

Thread Length:

0.320 inches

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625, type 1 or 2 military specification single treatment response

Shell Material Specification:

Qq-a-250/8 federal specification single material response

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response or mil-p-19833, ty gdi-30f military specification single material response
single mating end

Shell Guide Type And Location Designator:

B slot

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28748/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.