NSN 5935-01-338-3516

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-338-3516

Body Style:

Straight shape, internal coupling

Overall Length:

1.070 inches

Overall Diameter:

0.560 inches

Cable Entrance Diameter:

0.110 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

10.0 gigahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy 360 single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end or plastic polystyrene single mating end or plastic polytetrafluoroethylene single end or plastic polytetrafl

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy 360

NSN 5935-01-338-3516

Electrical Plug Connector - Page 2 of 2



| Shell Surface Treatment: |
|--|
| Silver |
| Shell Surface Treatment Specification: |
| Qq-s-365 federal specification single treatment response |
| Shell Material Specification: |
| Qq-b-626 federal specification single material response |
| nsert Material Specification: |
| -p-403 federal specification 1st material response single mating end or mil-p-77, ty e-2 military specification 2nd material response single |
| mating end or mil-p-22748, cl a, grade 5 military specification 4th material response single mating end |
| ncluded Contact Quantity: |
| 1 single mating end single contact grouping |
| ncluded Contact Type: |
| Coaxial pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact and body surfaces silver |
| Precious Material And Weight: |
| 0.105 silver grains, troy |
| Precious Material: |
| Silver |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| 4039b0 |
| Mil-std (military Standard): |
| Mil-p-77 spec. |
| |
| |