Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-338-3518

### **Body Style:**

Straight type

### Overall Length:

Between 5.745 inches and 5.755 inches

### **Overall Height:**

Between 0.555 inches and 0.575 inches

### **Overall Width:**

Between 0.715 inches and 0.725 inches

#### **Environmental Protection:**

Vibration resistant and corrosion resistant and shock resistant and humidity resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.095 inches and 0.105 inches

#### Distance Between Mounting Facility Centers:

Between 5.445 inches and 5.455 inches

#### Mating End Quantity:

1

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

### **Polarization Method:**

Mating end

### **Connector Locking Method:**

Friction

### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# **Insert Material:**

Plastic polyphenylene single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1

federal specification 2nd treatment response single mating end single contact grouping

# **Terminal Type:**

Printed circuit single mating end single contact grouping

# **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

# Insert Material Specification:

Mil-m-24519, ty gst-40f military specification single material response single mating end



Included Contact Quantity:

368 single mating end single contact grouping

### Included Contact Type:

Flat pin single mating end single contact grouping

# Precious Material And Location:

Contact surfaces gold

# **Precious Material And Weight:**

0.368 gold grains, troy

### **Precious Material:**

Gold

### **Supplementary Features:**

Mounting method - unthreaded hole

Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.