

View Online at https://aerobasegroup.com/nsn/5935-01-338-3538

View Online at https://aerobasegroup.com/nsn/5935-01-338-3538
Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Hood, side opening w/clamp
Overall Length:
1.562 inches
Overall Height:
2.619 inches
Overall Width:
0.567 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Cable Entrance Diameter:
0.220 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Polarization Method:
Jackscrew and shell
Shell Type:
Hood, side opening
Connector Locking Method:
Jackscrew-socket
Connector Cable Strain Relief Method:
Cable clamp
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize



Shell Surface Treatment Specification:

Mil-a-8625, type 1 or type 2 military specification single treatment response

Shell Material Specification:

Qq-a-250/8, temper h32 federal specification single material response

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response or mil-p-19833, ty gdi-30f military specification single material response single mating end

Shell Guide Type And Location Designator:

B pin

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28748/4 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.