NSN 5935-01-338-7363

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-338-7363 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated from panel **Identification Code Color:** Yellow **Body Style:** Threaded bushing mounted **Overall Length:** 42.4 millimeters **Mounting Bushing Length:** 24.65 millimeters **Body Length:** 31.0 millimeters **Overall Diameter:** 12.7 millimeters **Bushing Accommodation Hole Shape:** Round w/flat **Maximum Voltage Rating In Volts:** 2500.0 ac **Accommodated Finger Type:** Banana spring single finger **Finger Accommodation Diameter:** 4.22 millimeters single finger **Finger Accommodation Length:** 23.37 millimeters single finger **Bushing Thru-hole Accommodation Length:** 8.89 millimeters **Bushing Thru-hole Accommodation Width:** 9.53 millimeters **Current Rating In Amps:** 3.0 **Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:**

0.250 inches **Terminal Type:**

Wire wrap

NSN 5935-01-338-7363

Tip Jack - Page 2 of 2



Material:
Bronze terminal
Material:
Plastic polycarbonate insulator
Precious Material And Location:
Spring and terminal surfaces gold
Precious Material:
Gold
Surface Treatment:
Nickel bushing
Surface Treatment:
Nickel bushing
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03400