

View Online at <https://aerobasegroup.com/nsn/5935-01-338-7370>

Thread Direction:

Right-hand

Overall Length:

1.336 inches

Overall Height:

0.630 inches

Overall Width:

0.390 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

End Application:

Forrestal class cv; arleigh burke class ddg; tarawa class lha; austin ship class lpd-4 amphibious transport docks; wasp class lhd; nimitz class cvn; spruance class dd (963); los angeles class ssn (688); oliver perry class ffg; ticonderoga class cg (47); 6625-01-196-8119 counter, electronic

Thread Size:

3.0 millimeters

Thread Pitch In Millimeters:

0.50

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Thread Tolerance Class:

6g internal

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Special Features:

Weapon system essential

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Iso s

Specification Data:

28480-1250-1782 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0