

View Online at <https://aerobasegroup.com/nsn/5935-01-338-7377>

**Body Style:**

Straight shape

**Overall Length:**

0.500 inches

**Overall Height:**

0.312 inches

**Overall Width:**

0.093 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

28.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**End Application:**

6625-01-272-3874 generator, signal

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Criticality Code Justification:**

Feat

**Terminal Type:**

Printed circuit single mating end single contact grouping

**Included Contact Quantity:**

5 single mating end single contact grouping

**Included Contact Type:**

Flat socket single mating end single contact grouping

**Special Features:**

Beryllium copper contacts in lieu of phosphor bronze

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Specification Data:**

28480-1200-1350 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0