

View Online at <https://aerobasegroup.com/nsn/5935-01-338-9263>

**Body Style:**

Right angle, type

**Overall Length:**

4.300 inches

**Overall Height:**

0.535 inches

**Body Width:**

0.385 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

**Distance Between Mounting Facility Centers:**

4.100 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

3 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Friction

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Printed circuit single mating end single contact grouping

**Guide Design And Location:**

D shape pin left-hand at 6 oclock d shape pin right-hand at 9 oclock

**Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:**

114 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.114 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.