NSN 5935-01-338-9451

Thread Class:

Thread Direction:

2b

Acme

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-338-9451

Right-hand Body Style: Straight shape, internal coupling Overall Length: 1.234 inches Overall Diameter: 0.969 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36100 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping					
Straight shape, internal coupling Overall Length: 1.234 inches Overall Diameter: 0.969 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36100 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Overall Length: 1.234 inches Overall Diameter: 0.969 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36100 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Overall Diameter: 0.969 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36100 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Overall Diameter: 0.969 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36100 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
O.969 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36100 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36100 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36100 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Mating End Quantity: 1 Contact Position Arrangement Style: 36100 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Contact Position Arrangement Style: 36100 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Contact Position Arrangement Style: 36100 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
36100 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Keyway or multiple keyway Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Insert Position In Deg: 0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
0.0 and 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Connector Locking Method: Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Internally threaded coupling ring Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
0.750 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Contact Material: Copper alloy single mating end single contact grouping Terminal Type:					
Copper alloy single mating end single contact grouping Terminal Type:					
Terminal Type:					
••					
Crimp single mating and single contact grouping					
Chilip single mating end single contact grouping					
Shell Material:					
Aluminum alloy					
Shell Surface Treatment:					
Nickel					
Included Contact Quantity:					
Included Contact Quantity: 6 single mating end single contact grouping					
·					
6 single mating end single contact grouping					

NSN 5935-01-338-9451

Electrical Plug Connector - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0