

View Online at <https://aerobasegroup.com/nsn/5935-01-339-1466>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

2.125 inches

**Overall Height:**

Between 1.344 inches and 1.406 inches

**Overall Width:**

Between 1.344 inches and 1.406 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.062 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.062 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.750 inches and 0.781 inches

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

18-19 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Length:**

0.290 inches and 0.664 inches

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 200.0 degrees celsius

**Thread Qty Per Inch (tpi):**

18 and 18

**Thread Size:**

1.062 inches and 1.125 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Rubber silicone class q single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Criticality Code Justification:**

Feat

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Included Contact Quantity:**

10 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

In order to complete the connector assembly, the user must obtain/provide the backshell, standard versions may be ordered as nsn 5935-01-177-9556, p/n m85049/52-1-18w for the straight style, or nsn 5935-01-174-3671, p/n m85049/51-1-18w for the right angle style; 16-22 wire size pin contacts in lieu of 16-16

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef and unef

**Specification Data:**

96906-ms3450 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.