

View Online at <https://aerobasegroup.com/nsn/5935-01-339-3223>

Body Style:

Right angle type

Overall Length:

2.858 inches

Overall Width:

0.353 inches

Body Height:

0.335 inches

Environmental Protection:

Heat resistant and cold resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

28.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

28.0 single mating end single contact grouping

Connector Locking Method:

Friction

End Application:

6625-01-272-3874 generator, signal

Operating Temperature Rating:

Between -40.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Square socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.050 gold grains, troy

Precious Material:

Gold

Specification Data:

28480-1251-7307 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.