

View Online at <https://aerobasegroup.com/nsn/5935-01-339-4075>

Body Style:

Straight shape

Overall Length:

6.400 inches

Overall Height:

1.059 inches

Overall Width:

0.350 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

0.122 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

3 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Features Provided:

Closed entry contact

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Guide Design And Location:

D shape socket left-hand at 3 oclock d shape pin right-hand at 6 oclock

Included Contact Quantity:

160 single mating end single contact grouping

Included Contact Type:

Hyperboloid single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.160 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.