NSN 5935-01-339-8468

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-339-8468

Body Style:

Right angle, type

Overall Length:

6.220 inches

Body Width:

0.366 inches

Unthreaded Mounting Hole Diameter:

0.071 inches

Distance Between Mounting Facility Centers:

5.900 inches

Mating End Quantity:

.

Contact Position Arrangement Style:

3 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

End Application:

Receiving set, sonar an/sqr-18 (v)

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Terminal Type:

Printed circuit single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode and unable to decode

Included Contact Quantity:

160 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

NSN 5935-01-339-8468

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Universal guide set
Precious Material And Location
Contact surfaces gold
Precious Material And Weight:
0.160 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0