## NSN 5935-01-339-8468

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-339-8468

**Body Style:** 

Right angle, type

**Overall Length:** 

6.220 inches

**Body Width:** 

0.366 inches

**Unthreaded Mounting Hole Diameter:** 

0.071 inches

**Distance Between Mounting Facility Centers:** 

5.900 inches

**Mating End Quantity:** 

.

**Contact Position Arrangement Style:** 

3 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Polarization Method:** 

Guide pin/socket

**Connector Locking Method:** 

Friction

**End Application:** 

Receiving set, sonar an/sqr-18 (v)

**Operating Tempurature Rating:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate glass filled single mating end

**Terminal Type:** 

Printed circuit single mating end single contact grouping

**Unable To Decode:** 

Unable to decode and unable to decode and unable to decode

**Included Contact Quantity:** 

160 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

## NSN 5935-01-339-8468

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Universal guide set
<b>Precious Material And Location</b>
Contact surfaces gold
<b>Precious Material And Weight:</b>
0.160 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0