NSN 5935-01-339-8470

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-339-8470

Body Style:

Angle shape, pcb type

Overall Length:

8.330 inches

Overall Height:

0.690 inches

Overall Width:

0.385 inches

Environmental Protection:

Vibration resistant and shock resistant and salt spray proof and thermal shock resistant

Unthreaded Mounting Hole Diameter:

Between 0.100 inches and 0.105 inches

Distance Between Mounting Facility Centers:

7.950 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

End Application:

Radar set an/spc-40c

Operating Tempurature Rating:

Between -55.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy 260 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-b-613 federal specification single material response single mating end single contact grouping

NSN 5935-01-339-8470

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Chromate
Shell Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Shell Material Specification:
Qq-a-200 federal specification single material response
Insert Material Specification:
$\label{eq:military specification single material response single mating end} \label{eq:military specification single material response single mating end} % \[\mathbf{Mil-m-14}, \mathbf{ty} \] \[\mathbf{Mil-m-14}, Mil-m-14$
Included Contact Quantity:
100 single mating end single contact grouping
Included Contact Type:
Flat pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.100 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.