Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-339-9600

## **Body Style:**

Straight shape

## **Overall Length:**

1.435 inches

## **Overall Height:**

1.416 inches

## **Overall Width:**

0.351 inches

## **Environmental Protection:**

Thermal shock resistant and salt spray proof and vibration resistant and shock resistant and humidity resistant

## **Unthreaded Mounting Hole Diameter:**

Between 0.090 inches and 0.100 inches

## Distance Between Mounting Facility Centers:

Between 1.210 inches and 1.220 inches

## Mating End Quantity:

1

# **Contact Position Arrangement Style:**

51 single mating end

# **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

200.0 single mating end single contact grouping

#### **Polarization Method:**

Mating end

#### Shell Type:

Solid

## **Connector Locking Method:**

Friction

## **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate glass filled single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping



	rminal Type:
	re lead single mating end single contact grouping
	ntact Material Specification:
	-w-343, ty s federal specification single material response single mating end single contact grouping
	ell Material:
	iminum alloy
	ell Surface Treatment:
	dmium and chromate
	ell Surface Treatment Specification:
	-p-416, type 2, cl 3 federal specification all treatment responses
	ell Material Specification:
Qq	-a-591 federal specification single material response
	ert Material Specification:
Mil	-m-14, ty sdg-f military specification single material response single mating end
Inc	luded Contact Quantity:
51	single mating end single contact grouping
Inc	luded Contact Type:
Ro	und pin single mating end single contact grouping
Pre	ecious Material And Location:
Co	ntact surfaces gold
Pre	ecious Material And Weight:
0.0	51 gold grains, troy
Pre	ecious Material:
Go	ld
Sh	elf Life:
N/a	à
Un	it Of Measure:
De	militarization:
No	
Fiig	g:
A03	39b0
Mil	-std (military Standard):
Mil	-g-45204 spec.