Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-340-0613

Body Style:	
Straight shape	
Overall Length:	
4.800 inches	
Overall Height:	
Between 0.808 inches and 0.834 inches	
Overall Width:	
0.580 inches	
Unthreaded Mounting Hole Diameter:	
Between 0.061 inches and 0.065 inches	
Distance Between Mounting Facility Centers:	
4.550 inches	
Mating End Quantity:	
1	
Contact Removability:	
Removable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
2.0 single mating end single contact grouping	
Polarization Method:	
Mating end	
Shell Type:	
Solid	
Connector Locking Method:	
Friction	
Operating Tempurature Rating:	
Between -55.0 degrees celsius and 150.0 degrees celsius	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping and nickel single mating end single contact grouping	
Insert Material:	
Plastic single mating end	
Contact Surface Treatment Specification:	
Mil-g-45204, type 1, cl 00, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290	
federal specification 2nd treatment response single mating end single contact grouping	
Terminal Type:	
Wire lead single mating end single contact grouping	
Contact Material Specification:	
Qq-c-530, half hard federal specification single material response single mating end single contact grouping	
Shell Material:	

Aluminum alloy

NSN 5935-01-340-0613

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Nickel Shell Surface Treatment Specification: Mil-c-26074 military specification single treatment response **Shell Material Specification:** Asm 4150 assn standard single material response **Included Contact Quantity:** 300 single mating end single contact grouping **Included Contact Type:** Brush pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.300 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.