NSN 5935-01-340-0625

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-340-0625 **Body Style:** Rectangular shape **Overall Length:** 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.700 inches **Overall Height:** 1.470 inches **Overall Width:** 1.100 inches **Environmental Protection:** Heat resistant and cold resistant and vibration resistant and shock resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.800 inches

Mating End Quantity:

Contact Position Arrangement Style:

106 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

End Application:

Receiving set, sonar an/sqr-18 (v)

Operating Tempurature Rating:

Between -65.0 degrees celsius and 150.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Wire wrap single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

NSN 5935-01-340-0625

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Quantity:
----------	---------	------------------

106 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.106 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.