Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-340-0629

#### **Body Style:**

Straight shape

## **Overall Length:**

1.950 inches

# **Overall Height:**

0.947 inches

## **Overall Width:**

0.360 inches

**Body Length:** 

1.760 inches

#### **Environmental Protection:**

Corrosion resistant and fungus resistant and humidity resistant and shock resistant and vibration proof

## **Unthreaded Mounting Hole Diameter:**

0.112 inches

## **Distance Between Mounting Facility Centers:**

1.600 inches

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

## Contact Removability:

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

## **Connector Locking Method:**

Latch

#### **End Application:**

Receiving set, sonar an/sqr-18a

## **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Insert Material:**

Plastic polyester glass filled single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Printed circuit single mating end single contact grouping



#### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-24519, ty gpt-20f or gpt-30f military specification single material response single mating end **Included Contact Quantity:** 20 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.