NSN 5935-01-340-1890

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-340-1890

Body Style:
Right angle type
Overall Length:
6.150 inches
Overall Height:
1.000 inches
Overall Width:
0.440 inches
Unthreaded Mounting Hole Diameter:
Between 0.123 inches and 0.130 inches
Distance Between Mounting Facility Centers:
5.850 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -55.0 degrees celsius and 105.0 degrees celsius
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy 260 single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping
Criticality Code Justification:
Feat
Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-613, half hard federal specification single material response single mating end single contact grouping

NSN 5935-01-340-1890

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Chromate
Shell Surface Treatment Specification:
Mil-c-5541, cl 1a military specification single treatment response
Shell Material Specification:
Qq-a-200/8, temper t6510 federal specification single material response
Included Contact Quantity:
104 single mating end single contact grouping
Included Contact Type:
Flat pin single mating end single contact grouping
Special Features:
Ground bushing installed at contact position 105
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.104 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.