NSN 5935-01-340-1893

Body Style: Straight type

Contact Material Specification:

material response single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-340-1893

Overall Length:
7.295 inches
Overall Height:
1.223 inches
Overall Width:
0.490 inches
Environmental Protection:
Humidity resistant
Unthreaded Mounting Hole Diameter:
Between 0.122 inches and 0.127 inches
Distance Between Mounting Facility Centers:
6.975 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Operating Tempurature Rating:
75.0 degrees celsius
Features Provided:
Low insertion force contact
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Tin single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end
Terminal Type:
Wire wrap single mating end single contact grouping

Qq-b-626 federal specification single material response single mating end single contact grouping and qq-c-530 federal specification single

NSN 5935-01-340-1893

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, ty sdg-f or ty gdi-30f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or gst-40f military specification 2nd material response single mating end

Included Contact Quantity:

180 single mating end single contact grouping

Included Contact Type:

Brush pin single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.