# NSN 5935-01-340-5707

**Body Style:**Straight shape

**Terminal Type:** 

Solder well single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-340-5707

| Overall Length:   |
|---|
| 6.220 inches  |
| Overall Height:   |
| 0.744 inches  |
| Overall Width:  |
| 0.366 inches  |
| Environmental Protection:   |
| Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant                                   |
| Unthreaded Mounting Hole Diameter:  |
| 0.110 inches  |
| Distance Between Mounting Facility Centers:   |
| 5.900 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 160 single mating end   |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping  |
| Contact Maximum Current Rating In Amps:   |
| 5.0 single mating end single contact grouping   |
| Polarization Method:  |
| Guide pin/socket  |
| Connector Locking Method:   |
| Friction  |
| End Application:  |
| Receiving set, sonar an/sqr-18 (v)  |
| Operating Tempurature Rating:   |
| Between -65.0 degrees celsius and 125.0 degrees celsius   |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping   |
| Insert Material:  |
| Plastic diallyl phthalate glass filled single mating end  |
| Contact Surface Treatment Specification:  |
| Mil-g-45204, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1, grade d federal |
| specification 2nd treatment response single mating end single contact grouping  |

## NSN 5935-01-340-5707

Electrical Receptacle Connector - Page 2 of 2



#### **Guide Design And Location:**

Key shape pin left-hand at 3 oclock and key shape pin right-hand at 3 oclock

### **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

### **Included Contact Quantity:**

160 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.160 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.