Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-340-7459

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
2.160 inches
Overall Height:
Between 1.802 inches and 1.822 inches
Overall Width:
Between 1.802 inches and 1.822 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.500 inches
Distance From Mounting Shoulder To Front Face:
Between 0.785 inches and 0.790 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
25-35 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
116.0 and 160.0 and 191.0 and 311.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
End Application:
Milstar
Thread Size:
1.625 inches
Terminal Location:
Back single mating end single contact grouping

NSN 5935-01-340-7459

Electrical Receptacle Connector - Page 2 of 2



Criticality Code Justification:
Feat
Terminal Type:
Printed circuit single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and nickel
Included Contact Quantity:
128 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Nuclear hardness critical item
Thread Series Designator:
Special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0