Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-340-7462

Body Style: Straight shape, flush mount **Overall Length:** 1.634 inches **Overall Height:** Between 1.997 inches and 2.027 inches **Overall Width:** Between 1.985 inches and 2.015 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.118 inches and 0.122 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.720 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.437 inches **Distance From Mounting Shoulder To Front Face:** 1.569 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** "106, a106" single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate glass filled single mating end or plastic epoxy single mating end or plastic phenolic single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy

NSN 5935-01-340-7462

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

Insert Material Specification:

Mil-m-14, ty gdi-30f or sdg-f military specification 1st material response single mating end or allied chemical 1288 bx mfr ref 2nd material response single mating end or mil-m-14 military specification 3rd material response single mating end

Included Contact Quantity:

106 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

D-shaped guide pins supplied loose

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.106 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-81659/31 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.