## NSN 5935-01-340-7469

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-340-7469

**Body Style:** Straight shape **Overall Length:** 0.886 inches **Overall Height:** 0.593 inches **Overall Width:** 0.228 inches **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 1.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 28.0 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction **End Application:** 6625-01-225-0087 meter, impedance **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Included Contact Quantity:** 10 single mating end single contact grouping **Included Contact Type:** Square pin single mating end single contact grouping

**Precious Material And Location:** 

Contact and terminal surfaces gold

## NSN 5935-01-340-7469

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Specification Data:
28480-1251-7406 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.