# NSN 5935-01-340-8638

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-340-8638 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.340 inches **Overall Height:** 0.650 inches **Overall Width:** 0.308 inches **Environmental Protection:** Moisture resistant and salt water resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.091 inches and 0.101 inches **Distance Between Mounting Facility Centers:** Between 2.093 inches and 2.107 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 37 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end and jackscrew **Shell Type:** Potting **Connector Locking Method:** Post jacksocket **Connector Cable Strain Relief Method:** Potting type Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

# NSN 5935-01-340-8638

Electrical Receptacle Connector - Page 2 of 3



#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end or plastic polyphenylene single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Contact Material Specification:**

Qq-w-343, type s federal specification single material response single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Nickel

#### **Shell Surface Treatment Specification:**

Mil-c-26074, class 3 military specification single treatment response

#### **Shell Material Specification:**

Qq-a-591 federal specification single material response

#### **Insert Material Specification:**

Mil-m-14, type sdg-f military specification 1st material response single mating end or mil-m-24519 military specification 2nd material response single mating end

## **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

37 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

# **Special Features:**

Jackscrew type-female and location-right handandjackscrew type-female and location-left hand

#### **Precious Material And Location:**

Contact and terminal surfaces gold

## **Precious Material And Weight:**

0.037 gold grains, troy

## **Precious Material:**

Gold

#### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

# **Unit Of Measure:**

# Demilitarization:

No

## Fiig:

A039b0

# NSN 5935-01-340-8638

Electrical Receptacle Connector - Page 3 of 3



Mil-std (military Standard):

Mil-g-45204 spec.