

View Online at <https://aerobasegroup.com/nsn/5935-01-340-9099>

Body Style:

Straight shape threaded

Overall Length:

0.828 inches

Overall Diameter:

1.078 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration resistant and hermetic

Distance From Mounting Shoulder To Front Face:

Between 0.591 inches and 0.722 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.125 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

5 number 20 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

End Application:

5855-01-173-0808

Thready Qty Per Inch (tpi):

24

Thread Size:

0.812 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment Specification:

Tt-c-490, type i military specification single treatment response single mating end single contact grouping and mil-p-53022, type i military specification single treatment response single mating end single contact grouping and mil-c-46168, type i military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Included Contact Quantity:

6 single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-53022 spec.