Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-340-9100

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, pcb, external coupling
Overall Length:
0.700 inches
Overall Height:
0.236 inches
Overall Width:
0.236 inches
Distance From Mounting Shoulder To Front Face:
0.535 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Smb single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
End Application:
6625-01-225-0087 meter, impedance
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic single mating end



Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material: Copper alloy **Shell Surface Treatment:** Gold and nickel **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact and body surfaces gold **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold **Supplementary Features:** Mounting method - jam mut **Thread Series Designator:** Unf **Specification Data:** 28480-1250-1777 manufacturers specification control Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0