

View Online at <https://aerobasegroup.com/nsn/5935-01-340-9902>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.630 inches

**Overall Diameter:**

0.700 inches

**Environmental Protection:**

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Sc 1st mating end

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Contact Maximum Frequency Rating:**

11.0 gigahertz all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thready Qty Per Inch (tpi):**

24 and 24

**Thread Size:**

0.625 inches and 0.688 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Insert Material:**

Plastic fluorinated ethylene propylene or plastic polytetrafluoroethylene all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification single treatment response all mating ends single contact grouping

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Passivate

**Insert Material Specification:**

L-p-389 federal specification 1st material response or I-p-403 federal specification 2nd material response all mating ends

**Included Contact Quantity:**

1 2nd mating end single contact grouping

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.